

CONFREE stand shower, round curved piezo water section shower head MAXI tap, piezo push-button, battery, DN15



CONFREE freestanding shower, stainless steel, thermostat, piezo switch, DN15, round design

For stand shower CONFREE with frost protection line 24 V/DC. Electronic shower device, stand housing made of stainless steel, triggering via very easy-to-operate piezo pushbutton, with use-dependent and adjustable hygiene flushing, CONHEAD MAXI nozzle shower head, for connection to cold or mixed water, for stand mounting.

Consisting of:

- Piezo switch, blue coloured ring, rosette high-gloss chromed
- Solenoid valve 6 V/DC ROBUST, bistable, in cartridge design, with connecting cable and connector plug
- CONHEAD-MAXI jet shower head: fixed, heavy solid brass version, with three single jet nozzles, low maintenance, low aerosol, chrome plated
- Freestanding casing: made of stainless steel, V4A, 1.4404, brushed stainless steel with a large, waterproof inspection cover for easy installation and maintenance, with a stable base flange, with 4 mounting holes
- Connection: fitting (clamp connector) for PE pipe Ø 25 mm
- curved version

- Battery, lithium 6 V, waterproof sealed with connection cable and connector plug

Base functions:

- Water flow time: 30 s factory setting (3-180 s) with start/stop function
- Hygienic flush factory setting: 30 s water flush after 12 h of last water flow activation (12, 24, 72 h adjustable or may be disabled)

Attributes:

Nominal connection width: DN15, 1/2 inch

Use: Piezo push button, with electronic start/stop-button

Mixture: No temp. mixing, for cold or premixed water

Power supply: Mains operation,

Sorting: 283,

Technical Data:

Operating voltage: 6 V/DC

Operating pressure: 1,0 – 5,0 bar

Flow rate: 0,15 l/s

Connection: Connection fitting (compression connector) for PE pipe Ø 25 mm

Protection class: IP68 (electronic components)

Dimensions (ØxH): 104x2200 mm

Foot flange (ØxH): 230x10 mm