


lino multiple washing system W35, chrome, IR-sensor, Click-plus, battery, COMFORT - with thermostat, R3/4



lino multiple washing system W35, with IR sensor, with thermostat, chromed

Pre-assembled multiple faucet assembly kit with touchless lino exposed wall-mounted faucets W35, chromed, distribution lines in a surface-mounted stainless steel distributor, for wall mounting.

- Sturdy version, valve body DZR-brass
- Reliable solenoid valve ROBUST (minimal level of water pressure surge) and economic aerator
- Stiff spout and fixed sensor
- Dual infrared sensors (with automatic setting feature), microprocessor
- Temporary-off (cleaning) and continuous water flow time (filling of basin) activated by Click-plus
- Continuous water flow adjustable with Click
- Temperature adjustable (with reliable thermostatic cartridge)
- With anti-scalding and auto-thermic protection
- 12, 24 or 48-hour hygienic flush activatable with Click
- Compatible with Service Monitor: control of stored operational data, settings and control functions

Battery:

6 V Lithium CRP2 - commercial; life time up to 4 years

Notice:

Service APP only available in conjunction with BLE Converter - no permanent evaluation option.

When using the Service APP, the BLE Converter must be ordered separately.

Attributes:

Faucets: 5 piece,

Nominal connection width: R3/4,

Use: IR-sensor, contact-free activation

Mixture: COMFORT - with thermostat, thermostatic mixer

Function key: Click-plus, exposed Click-plus button - continuous water flow, temporary-off

Power supply: Battery,

Spout (x): 280mm,

Colour: Chrome,

Sorting: 857,

Technical Data:

Battery: 6 V Lithium CRP2, life time up to 4 years
Operating pressure: 0,3 –10 bar
Water temperature (max.): 80 °C
Flow rate DN15: 4 l/min / 1 gpm (3 bar) per faucet
Follow-up time: 1 s pre-set (adjustable with 0-10 s)
Continuous water flow: 2 min pre-set (adjustable with 0,5-20 min)
Temporary-off: 2 min. (fixed)
Hygienic flush time: Adjustable with 3 sec.-20 min.; 2 min (fixed)
Sensor sensitivity: Automatic self-adapting sensor technology
Built-in filter: 0,5 mm mesh size
Aerator: Economic aerator, CASCADE (self-cleaning)
Sensorempfindlichkeit: permanent automatisch selbststeinmessend
Connection: R 3/4
Spout: 280 mm /10 °C
Mounting height: 350 - 450 mm above washbasin / gully
Fitting distance: 600 mm
Engineering standards: DIN EN 200; CE
Dimensions (HxD): 250x80 mm
Width (X): 3000 mm