


lino multiple washing system W35, chrome, IR-sensor, Click-plus, battery, COMFORT - with thermostat, R3/4



lino multiple washing system W35, with IR sensor, with thermostat, chromed

Pre-assembled multiple faucet assembly kit with touchless lino exposed wall-mounted faucets W35, chromed, distribution lines in a surface-mounted stainless steel distributor, for wall mounting.

- Sturdy version, valve body DZR-brass
- Reliable solenoid valve ROBUST (minimal level of water pressure surge) and economic aerator
- Stiff spout and fixed sensor
- Dual infrared sensors (with automatic setting feature), microprocessor
- Temporary-off (cleaning) and continuous water flow time (filling of basin) activated by Click-plus
- Continuous water flow adjustable with Click
- Temperature adjustable (with reliable thermostatic cartridge)
- With anti-scalding and auto-thermic protection
- 12, 24 or 48-hour hygienic flush activatable with Click
- Compatible with Service Monitor: control of stored operational data, settings and control functions

Battery:

6 V Lithium CRP2 - commercial; life time up to 4 years

Notice:

Service APP only available in conjunction with BLE Converter - no permanent evaluation option.

When using the Service APP, the BLE Converter must be ordered separately.

## Attributes:

Faucets: 6 piece,

Nominal connection width: R3/4,

Use: IR-sensor, contact-free activation

Mixture: COMFORT - with thermostat, thermostatic mixer

Function key: Click-plus, exposed Click-plus button - continuous water flow, temporary-off

Power supply: Battery,

Spout (x): 280mm,

Colour: Chrome,

Sorting: 858,

## Technical Data:

Battery: 6 V Lithium CRP2, life time up to 4 years  
Operating pressure: 0,3 –10 bar  
Water temperature (max.): 80 °C  
Flow rate DN15: 4 l/min / 1 gpm (3 bar) per faucet  
Follow-up time: 1 s pre-set (adjustable with 0-10 s)  
Continuous water flow: 2 min pre-set (adjustable with 0,5-20 min)  
Temporary-off: 2 min. (fixed)  
Hygienic flush time: Adjustable with 3 sec.-20 min.; 2 min (fixed)  
Sensor sensitivity: Automatic self-adapting sensor technology  
Built-in filter: 0,5 mm mesh size  
Aerator: Economic aerator, CASCADE (self-cleaning)  
Sensorempfindlichkeit: permanent automatisch selbststeinmessend  
Connection: R 3/4  
Spout: 280 mm /10 °C  
Mounting height: 350 - 450 mm above washbasin / gully  
Fitting distance: 600 mm  
Engineering standards: DIN EN 200; CE  
Dimensions (HxD): 250x80 mm  
Width (X): 3600 mm